Data current as of: 30-10-2026 15:53

Link to the product: https://www.icharger.eu/icharger-458-duo-dual-channel-charger-2200w-45a-lipo-2x8s-p-748.html



iCharger 458 DUO Dual Channel Charger 2200W 45A LiPo 2x8S

Price	**475.95 Euro**
Availability	**Not available**
Shipping time	**24 hours**
Producer code	**458 DUO**
Manufacturer	**iCharger**

Product description

iCharger 458 DUO Dual Channel Charger 2200W 45A LiPo 2x8S

Introducing the 458Duo iCharger - the most powerful iCharger yet! Don't let its familiar appearance fool you, this dual-port charger boasts 45A charge rates per channel, packing a massive 2200W output. Designed to exceed its predecessor, the 308Duo, the 458Duo features beefier input and output connections that can handle higher current levels. Its open-port style balance connections eliminate the need for separate balance boards, while the sleek IPS display and improved temperature ports make for a user-friendly experience. The charger also includes a USB-C fast-charge port for added convenience. With the 458Duo, you can simultaneously charge batteries with different cell counts at up to 45A per channel, and combine both channels for a blazing 70A charge rate. When it comes to charging, nothing beats the power and convenience of an iCharger.

Package:

- iCharger 458Duo
- Power cord DC
- Manual

Specification:

Input voltage range: 10—49VDC
Maximum Output voltage: 40VDC
Maximum input current limit: 70A(Channel 50A)
Maximum charge/discharge current: 70A(Channel 45Ax2)
Maximum charge power capacity: 2200W(Channel 1600Wx2)
Maximum discharge power capacity: 140W(Channel 80Wx2)
Maximum regenerative discharge power capacity: 2200W(Channel 1600Wx2)
Maximum extra discharge power capacity: 2200W (Channel 1600W @36V/45A)
Maximum current drain for balancing: 4A(Channel 2Ax2)
Type-C PD port: 5V/3A□ 9V/2A□ 12V/1.5A
Support Battery type□ LiPo, Lilo, LiFe, LiVH, LTO, NiZn, NiMH, NiCd, Pb

Net weight: 930g
Dimension: 171×118×57 ±0.5mm

Specification:

Specification:

Input voltage range: 10—49VDC
Maximum Output voltage: 40VDC
Maximum input current limit: 70A(Channel 50A)
Maximum charge/discharge current: 70A(Channel 45Ax2)
Maximum charge power capacity: 2200W(Channel 1600Wx2)
Maximum discharge power capacity: 140W(Channel 80Wx2)
Maximum regenerative discharge power capacity: 2200W(Channel 1600Wx2)
Maximum extra discharge power capacity: 2200W (Channel 1600W @36V/45A)
Maximum current drain for balancing: 4A(Channel 2Ax2)
Type-C PD port: 5V/3A□ 9V/2A□ 12V/1.5A
Support Battery type□ LiPo, Lilo, LiFe, LiVH, LTO, NiZn, NiMH, NiCd, Pb
Net weight: 930g
Dimension: 171×118×57 ±0.5mm