

Link to the product: <https://www.icharger.eu/icharger-x6-800w-30a-lipo-6s-p-692.html>

## iCharger X6 800W 30A LiPo 6S



Price	<b>173.57 Euro</b>
Availability	<b>Available in stock</b>
Shipping time	<b>24 hours</b>
Producer code	<b>X6</b>
Manufacturer	<b>iCharger</b>

### Product description

## iCharger X6 800W 30A LiPo 6S

The Jushi X6 Charger is the latest charger on the market that features an incredible power density never before seen! The X6 boasts a whopping 800W charge capabilities at up to 30A on appropriate input voltages. The balance circuit offers a power 2A circuit, allowing your batteries to be maintained at the highest levels of power possible. Featuring an excellent IPS color display, the X6 will be easily seen in all lighting sources. The X6 utilizes the famous and simplistic Jushi user interface, as well as standard logging & servo testing abilities.

### Features:

- X6 uses advanced Synchronous buck-boost DC/DC converter technology with high power, high current and high-performance power conversion circuit. The maximum charge power capacity is up to 800W, the maximum charge/discharge current of a channel is up to 30A.
- X6 Supports 6s LiPo, Lilo, LiFe, LiHV, LTO and NiZn batteries, with maximum 2A balance current, and adopts a unique balance calculation of internal resistance correction. Supports 1-20s NiMH/NiCd batteries and 1-12s Pb batteries.
- With digital-power mode for great protection (over-current protection, over-voltage protection, input under-voltage protection, input undercurrent protection, and etc.)
- Intelligent fan control. Sensing internal temperature via the internal temperature sensor, to thereby control the fan speed.
- Internal temperature protection. When the internal temperature exceeds the Power Reduce temperature, the output power is automatically reduced; and the charger will shut down when temperature exceeds the Shut-down temperature.
- This charger can save 32 parameters sets and support the data import/export to SD card. 7. A 2.4" IPS LCD screen provides rich information including current, voltage, power, capacity, internal resistance, control status, time-consuming and temperature, etc.
- Multi-discharge features: self-discharge, regenerative to input discharge, and lithium battery extra expanding discharge.
- Supports measurement for internal resistance of battery offline and online. Can measure not only the internal resistance of the entire battery pack, but also measure the internal resistance of each cell within the lithium battery.
- X6 has protection for reversed polarity (input or output), input voltage/current, battery temperature, charging capacity, overrun time and maximum power etc.
- Supports upgrading the hardware program by USB port or SD card. X6 also supports the "Jushi Console" software and can display, plot and analyze the charge and discharge data by it.

---

**Specifications:**

**Net weight:** 168g

**Dimension:** 83x65x37 ±0.5mm

**Input Voltage Range:** 10.0—32.0VDC

**Maximum Input Current Limit:** <35A

**Maximum Charge/Discharge Current:** 30A

**Maximum Charge Power Capacity:** 800W

**Maximum Discharge Power Capacity:** 30W

**Maximum Regenerative Discharge Power Capacity:** 800W

**Maximum Extra Discharge Power Capacity:** 900W @30V/30A

**Maximum Current Drain for Balancing:** >2A

**Includes:**

- (2) Input/Output Cables
- (1) CD Rom Manual

**Specyfifications:****Specifications:**

**Net weight:** 168g

**Dimension:** 83x65x37 ±0.5mm

**Input Voltage Range:** 10.0—32.0VDC

**Maximum Input Current Limit:** 2A